

Technical data sheet

Equipotential busbar 1804 for surface mounting

Item number: 5015557



- Mounted equipotential busbar 1804 in junction box
- Pre-marked junction box for inserting required cables and covers
- Contact strip made of nickel-plated brass
- Screws and clamp strap from hot-dip galvanised steel

Connection options:

- 6x cables 1.5–10 mm²
- 1x cable 6–16 mm²

PE Polyethylene

Master data

Item number	5015557
Description 1	Equipotential busbar
Description 2	for bathroom in housing
Manufacturer	OBO
Dimension	90,5x90,5x39
Colour	Light grey; RAL 7035
Material	Polyethylene
Smallest sales unit	10
Unit of quantity	Piece
Weight	8.077 kg
Weight unit	kg/100 pc.

Dimensions

Length	90.5 mm
Width	90.5 mm
Height	39.3 mm

Technical data sheet

Equipotential busbar 1804 for surface mounting

Item number: 5015557



Technical data

Quantity of flat conductor connections up to 30 mm	0
Quantity of flat conductor connections up to 40 mm	0
Quantity of cable connections up to 16 mm ² , rigid	1
Quantity of cable connections up to 25 mm ² , rigid	0
Quantity of cable connections up to 6 mm ² , rigid	6
Quantity of cable connections up to 95 mm ² , rigid	0
Quantity of round conductor connections 10 mm	0
Quantity of round conductor connections 8 mm	0
Quantity of round conductor connections 8-10 mm	0
Quantity of round conductor connections, total	7
Version for	In the housing
Type	Fixed structure
Insulator	yes
Surface of the terminal	Electrogalvanised
Surface of the contact rail	Nickel-plated
Material of the terminal	Steel
Material of the contact rail	Brass