


# Technical data sheet

AMS3518 anchor rail, slot 16.5 mm, BK, unperforated

Item number: 1112023



Central C profile rail for cable routing, in conjunction with clamp clips with a hammerhead foot. Can also be used as suspension construction for cable support systems.



**St** Steel

**BK** Bright

## Master data

Item number	1112023
Description 1	Profile rail
Description 2	unperforated, slot 16.5mm
Manufacturer	OBO
Dimension	2000x35x18
Material	Steel
Surface	Bright
Surface standard	
Smallest sales unit	2
Unit of quantity	Metre
Weight	116 kg
Weight unit	kg/100 m
CO Footprint (GWP) Cradle-to-Gate	1,9888 kg COe / 1 Meter


# Technical data sheet

AMS3518 anchor rail, slot 16.5 mm, BK, unperforated

Item number: 1112023



## Dimensions



Length	2,000 mm
Width	35 mm
Height	18 mm
Dimension L	2,000 mm

## Technical data

Breakable	no
Type of perforation	Without
Version for	Single profile
Bundle	20 m
Maintain electrical functions	no
Material thickness	2 mm
With perforation	no
With tothing	no
Profile shape	C profile
Slot width	16.5 mm
Static value A	1.48 cm <sup>2</sup>
Static value Iy	0.6 cm
Static value Iz	2.33 cm
Static value Wy	0.54 cm <sup>2</sup>
Static value Wz	1.33 cm <sup>2</sup>