

# Technical data sheet

## Clamp clip 2056, W-foot, single, metal pressure trough, FT

Item number: 1188307



Clamp clip with W-foot, metal pressure trough with rounded edges to protect the cable. For vertical and horizontal mounting of 1 single cable on angle irons < 40 mm. With 1-start screw thread on pressure trough, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for mounting indoors and outdoors. We recommend the use of a counter-trough.



St

Steel

FT

Hot-dip galvanised

### Master data

|                                    |                         |
|------------------------------------|-------------------------|
| Item number                        | 1188307                 |
| Type                               | BS-W1-M-22 FT           |
| Description 1                      | Clamp clip 2056         |
| Manufacturer                       | OBO                     |
| Dimension                          | 16-22mm                 |
| Material                           | Steel                   |
| Surface                            | Hot-dip galvanised      |
| Surface standard                   | DIN EN ISO 1461         |
| Smallest sales unit                | 100                     |
| Unit of quantity                   | Piece                   |
| Weight                             | 4.867 kg                |
| Weight unit                        | kg/100 pc.              |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,1462 kg COe / 1 Piece |


# Technical data sheet

Clamp clip 2056, W-foot, single, metal pressure trough, FT

Item number: 1188307



## Dimensions



|                  |         |
|------------------|---------|
| Length           | 22.5 mm |
| Width            | 27 mm   |
| Height           | 91 mm   |
| Plate thickness  | 1.5 mm  |
| Dimension A      | 22.5 mm |
| Dimension B      | 27 mm   |
| Dimension C      | 28 mm   |
| Dimension G (mm) | M6      |
| Dimension H      | 91 mm   |
| Dimension L      | 34 mm   |
| Dimension t      | 1.5 mm  |

## Technical data

|                               |                |
|-------------------------------|----------------|
| Number of cables/pipes        | 1              |
| For pipe diameter, max.       | 22 mm          |
| For pipe diameter, min.       | 16 mm          |
| Thread                        | M6             |
| Halogen-free                  | yes            |
| Length of external dimensions | 28 mm          |
| Max. Tightening torque        | 3 Nm           |
| With metal trough             | yes            |
| Mounting type                 | Angle profile  |
| Slot width                    | 10 mm          |
| Clamping range D, max.        | 22 mm          |
| Clamping range D, min.        | 16 mm          |
| Surface addition              | hot galvanised |
| Material addition             | Steel          |