Technical data sheet

MS4141 mounting rail, slot 22 mm, A4, perforated





Heavy-duty C profile rail for individual installation of support constructions, e.g. for cable trays or as a panel for switchgear cabinets. Can also be used for cable routing, in conjunction with clamp clips with a U foot.





A4

Stainless steel

2B

Bright, treated

Master data


Item number	1122990
Type	MSL4141P3000A4
Description 1	Profile rail
Description 2	perforated, slot 22mm
Manufacturer	OBO
Dimension	3000x41x41
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	3
Unit of quantity	Metre
Weight	201.1 kg
Weight unit	kg/100 m
CO Footprint (GWP) Cradle-to- Gate	10,1434 kg COe / 1 Meter

Technical data sheet

MS4141 mounting rail, slot 22 mm, A4, perforated



Item number: 1122990



Te	ch	nic	al	Ы	at	а

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Drill hole spacing, centre	50 mm
Maintain electrical functions	no
Hole size	14x28 mm
Material thickness	2 mm
With perforation	yes
With toothing	yes
Profile shape	C profile
Slot width	22 mm
Static value A	2.45 cm ²
Static value ly	5.18 cm
Static value Iz	7.56 cm
Static value Wy	2.51 cm ²
Static value Wz	2.69 cm ²