
Technical data sheet

Internal corner, without height adjustment unit

Item number: 7403826



Ready-to-mount internal corner, consisting of a trunking base, two lids, heightadjustable side profiles and brush bar arranged on the wall side for cable alignment. The scope of delivery contains one lid butt seal and a connector. For height adjustment five levelling units are required.





FS

Strip galvanized

Master data

Item number7403826TypeOKB IE 25085 ONDescription 1Internal cornerDescription 2with brush barManufacturerOBODimension421x421x87MaterialSteelSurfaceStrip galvanizedSurface standardDIN EN 10346Smalleet sales unit1		
Description 1Internal cornerDescription 2with brush barManufacturerOBODimension421x421x87MaterialSteelSurfaceStrip galvanizedSurface standardDIN EN 10346	Item number	7403826
Description 2with brush barManufacturerOBODimension421x421x87MaterialSteelSurfaceStrip galvanizedSurface standardDIN EN 10346	Туре	OKB IE 25085 ON
ManufacturerOBODimension421x421x87MaterialSteelSurfaceStrip galvanizedSurface standardDIN EN 10346	Description 1	Internal corner
Dimension 421x421x87 Material Steel Surface Strip galvanized Surface standard DIN EN 10346	Description 2	with brush bar
Material Steel Surface Strip galvanized Surface standard DIN EN 10346	Manufacturer	OBO
Surface Strip galvanized Surface standard DIN EN 10346	Dimension	421x421x87
Surface standard DIN EN 10346	Material	Steel
	Surface	Strip galvanized
Smallest sales unit 1	Surface standard	DIN EN 10346
	Smallest sales unit	1
Unit of quantity Piece	Unit of quantity	Piece
Weight 850 kg	Weight	850 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.


Technical data sheet

Internal corner, without height adjustment unit

Item number: 7403826



Dimensions 0 10



L	ength	421 mm
V	Vidth	250 mm
Н	leight	93 mm
D	Dimension h	93 mm

Technical data

85

Mounting opening cover	no
Floor plate	yes
Floor care	Dry
Cover fastening, locking	no
Seal installation option	no
Installation opening for on-floor tank	no
Decouplable	yes
Function	Internal corner
Suitable for expansion joint	no
Suitable for screed-flush closed underfloor ducts	no
Suitable for flushfloor, open un- derfloor trunking	yes
Suitable for screed-covered un- derfloor ducts	no
Minimum screed height	93
With connection opening	no
With equipotential bonding	no
With separating retainer	no
With overhang	yes
Height-adjustment range, min.	0 mm
Removable cover	yes
Separating retainer fastening	stecken
Separating retainer fastening	Plug