

# Technical data sheet

## PRO 55 device installation trunking, trunking width 100

Item number: 6132930



PROFILA NF device installation trunking for covered cable routing and device installation in internal areas.

Direct wall mounting using base perforation. Hardly inflammable and self-extinguishing after removal of a naked flame. Change the direction with the fittings and close the trunking ends with end pieces.

Base and cover in set.



**PVC** Polyvinylchloride

### Master data

Item number	6132930
Type	PRO 10055 blc
Description 1	Device installation trunking
Description 2	PROFILA SET 55x100 9010
Manufacturer	OBO
Colour	Pure white; RAL 9010
Material	Polyvinylchloride
Smallest sales unit	16
Unit of quantity	Metre
Weight	123.2 kg
Weight unit	kg/100 m

### Dimensions

Length	2,000 mm
Width	100 mm
Height	53 mm

# Technical data sheet

PRO 55 device installation trunking, trunking width 100

Item number: 6132930



## Technical data

Number of covers	1
Number of insertable partitions	1
Rear panel version (inner side)	Continuous DIN rail
Rectangular shape	yes
Halogen-free	no
Cable retaining clip	no
Duct connector	yes
Cover mounting type	Internal
Mounting perforation in base	yes
Usable cross-section	4440 mm <sup>2</sup>
Cover supplied	yes
Cover width	79 mm
Protection rating	IP40
Protective film	yes
Protection rating IK code	IK07.
Symmetrical	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C