Technical data sheet

AR45 socket unit, single

Item number: 6119401





Pre-terminated socket unit without labelling panel, suitable for installation in Rapid 80 device installation trunking systems.

Socket unit, consisting of:

- Accessory mounting box, single, type 71GD8-2
- Protective contact socket, single, 0° connection direction, colour: see table
- Cover frame AR45, single, without labelling panel, colour: pure white For installation in Rapid 80 device installation trunking and ISS service poles.

PC

Polycarbonate

Master data

Item number	6119401
Description 1	Socket unit
Description 2	for single Modul 45
Manufacturer	OBO
Dimension	84x84x59mm
Colour	Pure white; RAL 9010
Material	Polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	10.7 kg
Weight unit	kg/100 pc.
CO Footprint (GWP) Cradle-to- Gate	0,5763 kg COe / 1 Piece

Technical data sheet


AR45 socket unit, single

Item number: 6119401



Dimensions 09

Width	84 mm
Height	84 mm



Technical data

Cover Complete housing Closable no Connection type Screwless terminal Number of units 1 Number of modules (for modular construction)	
Connection type Number of units Number of modules (for modular construction) Screwless terminal 1 0	
Number of units Number of modules (for modular construction) 1 0	
Number of modules (for modular construction)	
construction)	
Normalian of avoitable black and late	
Number of switchable sockets 0	
Number of poles 2	
Printed label/coding Without printing	
Version for Single 0°	
Surface version Matt	
Version for SCHUKO	
Ejection mechanism no	
Fastening type Lock	
Labelling panel no	
increased touch protection yes	
Error current protection no	
For more difficult conditions (according to VDE)	
Power reserve no	
Halogen-free yes	
Insulated installation no	
Hinged cover no	
Coding	
Warning light no	
With on/off switch no	
With fine-wire fuse no	

Technical data sheet AR45 socket unit, single

Item number: 6119401



Technical data		
	With functional lighting	no
	With orientation lighting	no
	Mounting type	Device installation duct
	Nominal voltage	250 V
	Nominal current	16 A
	Protection rating	Other
	Special power supply	Without special power supply
	Socket version	Protective contact
	Socket angle	0°
	Depth	60 mm
	Transparent	no
	Rotated central insert	no
	Surge protection	no